

8A4DLTP-DEKA

SPECIFICATIONS

| | |
|-----------------------------|------------------------------|
| Nominal Voltage (V) | 12V |
| Capacity at C/100 | 210Ah |
| Capacity at C/20 | 198Ah |
| Weight | 129 lbs. (59 kg) |
| Plate Alloy | Lead Calcium |
| Posts | Forged Terminals & Bushings |
| Container/Cover | Polypropylene |
| Operating Temperature Range | -40°F (-40°C) - 140°F (60°C) |

For Charging Parameters please refer to www.mkbattery.com

Click on Technical Data, then on Photovoltaic Charging Parameters in the PV/Solar section

| | |
|----------|--------------|
| Vent | Self-sealing |
| Terminal | T (T975) |



Made in the U.S.A. by East Penn Manufacturing Co., Inc.

Distributed by:

Valve-Regulated, Absorbed Glass Mat Technology




DIMENSIONS

Inches (mm)

| | |
|--------|----------------|
| Length | 20.73 (527 mm) |
| Width | 8.44 (214 mm) |
| Height | 10.82 (275 mm) |

AGM Cycle Life vs Depth of Discharge at +25°C (77°F)
Based on BCI 2-hour Capacity



MK Battery

1631 South Sinclair Street • Anaheim, California 92806

Toll Free: 800-372-9253 • Fax: 714-937-0818 • E-mail: sales@mkbattery.com

